

## DS-T200



### Key Features

- 2 Megapixel high-performance CMOS
- Analog HD output, up to 1080P resolution
- True Day/Night, Smart IR
- Up to 20m IR distance
- IP66 weatherproof

## Specifications

| <b>Camera</b>        |                                                                         |
|----------------------|-------------------------------------------------------------------------|
| Image Sensor         | 2MP CMOS Image Sensor                                                   |
| Signal System        | PAL/NTSC                                                                |
| Effective Pixels     | 1920(H)*1080(V)                                                         |
| Min. illumination    | 0.01 Lux @ (F1.2,AGC ON),0 Lux with IR                                  |
| Shutter Time         | 1/25(1/30)s to 1/50,000s                                                |
| Lens                 | 2.8mm, 3.6mm, 6mm optional                                              |
|                      | Angle of View: 103°(2.8mm), 82.2°(3.6mm), 54°(6mm)                      |
| Lens Mount           | M12                                                                     |
| Day & Night          | ICR                                                                     |
| Angle Adjustment     | Pan: 0 - 360°, Tilt: 0 - 180°, Rotation: 0 - 360°                       |
| Synchronization      | Internal synchronization                                                |
| Video Frame Rate     | 1080p@25fps/1080p@30fps                                                 |
| HD Video Output      | 1 Analog HD output                                                      |
| S/N Ratio            | >62dB                                                                   |
| <b>General</b>       |                                                                         |
| Operating Conditions | -40 °C – 60 °C (-40 °F – 140 °F), Humidity 90% or less (non-condensing) |
| Power Supply         | 12 VDC ± 15%                                                            |
| Power Consumption    | Max. 4W                                                                 |
| Protection Level     | IP66                                                                    |
| IR Range             | Up to 20m                                                               |
| Dimensions           | Φ70×149.5mm (Φ2.76"×5.89")                                              |
| Weight               | 400g                                                                    |

## Dimensions

